

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/747,770	12/22/2000	Ron J. Vandergeest	0500.0008171 (10500.00.81	4395
23418	7590 03/11/2005		EXAM	INER
	RICE KAUFMAN &	но, тно	HO, THOMAS M	
222 N. LASALLE STREET CHICAGO, IL 60601				
			ART UNIT	PAPER NUMBER
			2134	

DATE MAILED: 03/11/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)			
-	09/747,770	VANDERGEEST ET AL.			
Office Action Summary	Examiner	Art Unit			
	Thomas M Ho	2134			
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply					
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication. - If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely. - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication. - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).					
Status					
1) Responsive to communication(s) filed on 13 S	September 2004.				
2a)☐ This action is FINAL . 2b)☒ This	s action is non-final.				
3) Since this application is in condition for allowance except for formal matters, prosecution as to the merits is					
closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.					
Disposition of Claims					
4)⊠ Claim(s) <u>1-31</u> is/are pending in the application.					
4a) Of the above claim(s) is/are withdrawn from consideration.					
5)☐ Claim(s) is/are allowed.					
6)⊠ Claim(s) <u>1-26</u> is/are rejected.					
7)☐ Claim(s) <u>27-31</u> is/are objected to.					
8) Claim(s) are subject to restriction and/or election requirement.					
Application Papers					
9) The specification is objected to by the Examiner.					
10)☐ The drawing(s) filed on is/are: a)☐ accepted or b)☐ objected to by the Examiner.					
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).					
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).					
11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.					
Priority under 35 U.S.C. § 119					
12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).					
a) ☐ All b) ☐ Some * c) ☐ None of:					
1. Certified copies of the priority documents have been received.					
Certified copies of the priority documents have been received in Application No					
3. Copies of the certified copies of the priority documents have been received in this National Stage					
application from the International Bureau (PCT Rule 17.2(a)).					
* See the attached detailed Office action for a list of the certified copies not received.					
Attachment(s)	" .	1555 140)			
1) Notice of References Cited (PTO-892) 4) Interview Summary (PTO-413) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) Paper No(s)/Mail Date					
3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) 5) Notice of Informal	Patent Application (PTO-152)			
Paper No(s)/Mail Date	6)				
U.S. Patent and Trademark Office PTOL-326 (Rev. 1-04) Office A	action Summary	Part of Paper No./Mail Date 4			

Page 2

Application/Control Number: 09/747,770

Art Unit: 2134

DETAILED ACTION

- 1. Claims 1-31 are pending.
- 2. Claims 27-31 are allowable.

Response to Arguments

3. Applicant's arguments have been fully considered but are moot in view of the new grounds of rejection.

Claim Rejections - 35 USC § 103

- 4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 5. Claims 1-4, 6-26 are rejected under 35 U.S.C. 103(a) as being anticipated by Crane et al., US patent 6510236.
- 6. Claim 5 is rejected under 35 U.S.C. 103(a) as being unpatentable over Crane et al. US patent 6510236 and Bellare et al., US patent 5673318.

In reference to claim 1:

Application/Control Number: 09/747,770

Art Unit: 2134

Crane et al. discloses a method for providing user authentication comprising:

• sending, by a first unit, user identification data to an authentication unit, where the client sends via the first unit(the application server of Figure 4), user identification data(Column 4, lines 55-63) to the authentication unit, which is the device authentication server of (Figure 4, Item 18).

Page 3

- using the user identification data to determine which destination unit will receive the authentication code to authenticate the user, where the user identification data is used by the Application Server(Item 12) to access a database(Item 15) to determine which destination unit (which particular authentication server) will receive the authentication code to authenticate the user.(Column 5, lines 1-20)
- sending the authentication code to the determined destination unit based on the user identification data, where the authentication code(code used to authenticate the client) will be sent to the destination unit(the Application authentication server, Item 17), based on user identification data. (Column 5, lines 23-27)
- returning a response to the authentication unit (Column 5, lines 28-33)
- authenticating the user when the returned authentication code matches the sent authentication code, where the code is sent back to the user in the form of a token.
 (Column 5, lines 33-37)

Crane fails to explicitly disclose returning the authentication code to the authentication unit.

Crane instead discloses that merely a simple yes or no is returned that digitally signed.

Crane however teaches that all of the message, or a response string may be returned instead of a digital signature. (Column 5, lines 60-64) The string, as understood the invention of Crane discloses the authentication code, which includes the user ID. (Column 4, lines 55-64)

It would have been obvious to one of ordinary skill in the art to send the string authentication code instead of a simple yes no answer in view of the fact that Crane discloses this modification to his own invention.

In reference to claim 2:

Crane et al. (Column 5, lines 35-43) discloses a method including the step of generating the authentication code on a per authentication session basis and sending the authentication code to the determined destination unit in response to the generated authentication code, where authentication code is a token generated on a per session basis through the device id.

In reference to claim 3:

Crane et al. (Column 4, line 58 – Column 5, line 27) discloses a method including the step of maintaining per user destination unit data including at least one destination unit identifier per user and wherein the step of using the user identification data to determine which destination unit will receive the authentication code includes sending the authentication code to the determined destination unit based on the stored per user destination unit identifier, where the per user

destination unit identifier is the device ID, and the data of the user is maintained in a database

containing userIDs matched with device IDs.

In reference to claim 4:

Crane et al. (Column 4, line 48 – Column 5, line 36) discloses a method including the step of

receiving user input in response to the step of sending the authentication code and waiting to

return the authentication code to the authentication unit until receipt of the user input, where after

the authentication code is sent out the first time, the user enters in authentication data to be sent

off to the server, and where the Authentication code isn't returned until the user gives this input.

In reference to claim 5:

The combination of Crane et al. fails to disclose a method including the steps of:

Prior to returning the authentication code to the authentication unit, digitally signing, by the first

unit, the returned authentication code to produce a digitally signed authentication code that was

received from the determined destination unit,

Verifying the digitally signed authentication code as part of step (e),

Crane instead discloses

Returning the authentication code to the authentication unit. (Column 5, lines 28-33) & (Column

5, lines 60-65)

Verifying the authentication code as part of step (e) (Column 5, lines 33-37)

Crane does not disclose signing this authentication code prior to sending it back.

Bellare et al. (Figure 8) discloses a method that provides security, and digitally signs the authentication code. (Column 3, lines 58-64) Bellare et al. discloses their invention allows the receiver to be confident that a message claimed to be sent by the sender was really sent by that sender (Column 3, lines 15-20), and that this method also allows forgeries to be detected. (Column 3, lines 45-50)

It would have been obvious to one of ordinary skill in the art at the time of invention to use a digital signature to sign the authentication code in order to allow forgeries in the transmission of the authentication code to be detected.

Claim 9 is rejected for the same reasons as claim 5.

Claim 10 is substantially similar to claim 1 and is rejected for the same reasons. The additional wireless back limitation is discussed in claim 15.

In reference to claim 15:

Crane et al. (Column 1, lines 25-39) & (Column 6, line 1-14) discloses a method including the step of sending the authentication code on the wireless back channel[or data based on it] to the destination unit using at least one of a short message session(SMS) channel, a paging channel and a control channel, where it is understood that a wide variety of authentication devices is

Application/Control Number: 09/747,770

Art Unit: 2134

supported such as biometric scanners or token cards which are frequently known in the art to operate based on a RF (radio frequency) transmission.

In reference to claim 16:

Crane et al. (Column 5, lines 14-36) discloses a method including the step of validating the primary authentication information, where the device authentication server validates the primary authentication information.

Claims 17, 6 are rejected for the same reasons as claim 1.

Claims 22, 18, 11, 7 are rejected for the same reasons as claim 2.

Claims 23, 19, 12, 8 are rejected for the same reasons as claim 3.

Claims 24, 13 are rejected for the same reasons as claim 4.

Claims 25, 14 are rejected for the same reasons as claim 5.

Claim 20 is rejected for the same reasons as claim 9.

Claim 26 is rejected for the same reasons as claim 15.

Reasons for Allowance

7. The following discloses Examiner's reasons for allowance of claims 27-31.

In reference to claim 27:

Crane et al. (Column 4, line 48 – Column 5, line 53) discloses a system for providing user authentication comprising:

Application/Control Number: 09/747,770

Art Unit: 2134

• A first unit, where the first unit is the authentication device of the client.

• A second unit operatively coupleable to the first unit via a primary wireless channel and operatively coupleable to an authenticator, where the second unit is the application server of figure 4, and where the primary wireless channel is the wireless channel connecting the application server, with a wireless authentication device(biometric scanner, token reader (Column 3, lines 10-37)) of the client. (Figure 1, Items 16, 14)

Page 8

- A third unit, operatively coupleable to the second unit where the third unit is the device authentication server (Figure 4, Item 18), and the second device is the application server. (Figure 4, Item 12)
- The first unit operative to send primary authentication information via the primary channel during a session to the second unit, where the authentication information is the authentication string(Column 4, lines 52-64), and the first unit is the client, the second is the application server of (Figure 4)
- The authenticator operative to use the primary authentication information to determine which destination unit, other that the first unit, will receive an authentication code as a secondary authentication information via the wireless back channel and wherein the destination unit is the third unit, where the authenticator is the database device, (Item 15 of Figure 4), which goes and uses the authentication information to determine which destination unit(device server 18 of Figure 4) will receive the an authentication code.
- The second unit operative to the send the authentication code to the destination unit based on the primary authentication information sent via the primary channel during the same session (Figure 4, Item 2)

Crane et al fails to disclose the uses of a wireless connection between the second device and the third device. However, the Examiner notes that the use of wireless connections to connect one digital system to another is ubiquitous and has been in use at in radios since at least World War II. Other common embodiments include cell phones, wireless LANs, CBs, and PDAs. It would have been obvious to one of ordinary skill in the art at the time of invention to employ the use of wireless connections between the servers in order to provide the advantage of not having to purchase and maintain wires between them, and the provide the advantage of portability.

Crane also fails to explicitly a direct embodiment in which

 The authenticator operative to authenticate the user which the returned authentication code received from the wireless primary channel matches the sent authentication code that was sent.

Crane discloses directly that the authenticator returns a Y/N which is signed (Item 3, Figure 4) instead of an authentication code.

Crane however later discloses that a modification can be made to his device in which rather than sending a digital signature, a "String" may be returned. (Column 5, line 60-64). Crane defines a string in his invention to include the userid and device type among other authentication data. (Column 4, lines 52-63) These two pieces of information comprise the authentication code.

Page 10

Application/Control Number: 09/747,770

Art Unit: 2134

Because of this disclosure, the Examiner considers a modification in which Item 3, was modified to return the authentication string or (code) to be obvious in view of Crane. In other words, Crane with the modification mentioned discloses a method in which the authenticator, operative to authenticate the user(client) which the returned authentication code received from the wireless primary channel. (authentication device of client, Item 16, Figure 1) matches the authentication code that was sent. (Item 1, Figure 4)

No art can be found however that discloses a system for providing authentication in which

• The first unit operative to return the authentication code on the wireless primary channel to the second unit during the same session

The Examiner notes that while in the art, it is known that a client(first unit) with an authentication code, may send an acknowledgment of receipt, or an acknowledgement of integrity for the code to a second unit,

no art nor motivation to combine can be found in which the first unit(abiding by the claimed limitations set forth in Claim 27) would return the authentication code to the second unit during the same session.

For this reason, Claim 27 and its dependent claims are allowable.

Conclusion

6. Any inquiry concerning this communication from the examiner should be directed to

Thomas M Ho whose telephone number is (571)272-3835. The examiner can normally be reached on M-F from 9:30 AM - 6:00 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Gregory A. Morse can be reached on (571)272-3838.

The Examiner may also be reached through email through Thomas Ho6@uspto.gov

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is (571)272-2100.

General Information/Receptionist

Telephone: 571-272-2100

Fax: 703-872-9306

Customer Service Representative

Telephone: 571-272-2100

Fax: 703-872-9306

TMH

February 26th, 2005

TECHNOS.